







FR 795 SCC SMT

Full Extension Progressive Action Drawer Slide



Specifications

-  side mount
-  18.0 mm / 0.71 in.
-  dynamic up to 70 kg / 154 lbs.
-  solid synthetic rollers
-  stainless steel 1.4509 / 441
-  -25 °C to +80 °C
-13 °F to +176 °F


Characteristics

- high lateral stability
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- compatible with regular extension drawer slide FR 1052 SCC SMT
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

Mounting Type

- cabinet profile with bayonet mounting tabs and safety nose
- drawer profile without screw holes
- tool-less quick assembly of the cabinet profile

Dimensions



Length		Extension		Weight		Item No.	Item No.
				per set		PU 1	PU 2
mm	inch	mm	inch	kg	lbs.		
300	11.81	285	11.22	1.37	3.01	▶ 70440	▶ 70440GV
350	13.78	335	13.19	1.44	3.19	▶ 70441	▶ 70441GV
400	15.75	385	15.16	1.68	3.70	▶ 70442	▶ 70442GV
450	17.72	435	17.13	1.92	4.23	▶ 70443	▶ 70443GV
500	19.69	485	19.09	2.14	4.73	▶ 70444	▶ 70444GV
550	21.65	535	21.06	2.38	5.25	▶ 70445	▶ 70445GV
600	23.62	585	23.03	2.62	5.79	▶ 70446	▶ 70446GV
650	25.59	635	25.00	2.86	6.30	▶ 70447	▶ 70447GV
700	27.56	685	26.97	3.10	6.83	▶ 70448	▶ 70448GV
750	29.53	735	28.94	3.36	7.40	▶ 70449	▶ 70449GV

Packing Unit

PU 1 – Sets assembled per Box, all Lengths: 5

PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes

(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)

▶ in stock